



Technical Data Sheet

Brake and Clutch Fluid DOT 3 (C1-36)

The Brake Fluid DOT 3 is a high boiling synthetic brake fluid providing superior performance combined with a greater safety margin.



Quantity	250 ml / 450 ml
Barcode	
Box/Case	24 pcs

Brake and Clutch Fluid DOT 3 - DOT 3 is brake fluid for hydraulic braking systems of motor vehicles which is indented for operation in the temperature range from -50 °C to 240 °C. It meets the international standard DOT 3. It does not damage rubber and metal. It has good thermal stability, perfect protection against corrosion of ferrous as well as nonferrous metals.

Technical Specifications:

Aspect	Tin-Plate can
Color	Bright, clear pale amber liquid
pH (20 °C)	About 7 - 10
ERBP	230 °C
Relative Density	1.1 ~ 1.2 g/ml (20 °C)
Wet ERBP	149 °C

HOW TO USE:

As with all brake fluids which contain glycol ethers, care should be taken to avoid spilling this product on paint work as it may have a damaging effect. In case of spillage, rinse the affected area with water immediately. Do not wipe.

MODALITY OF STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions. Keep out of reach of children.

This information, even if reliable, must be considered only approximate. We are not responsible for the wrong use of the product, or the violation of any license. Before using, the users should verify the suitability of the product for its specific use.

BEFORE USE, CONSULT THE SAFETY DATA SHEET OF THE PRODUCT.

